



## CHIC 130 ERRE SASH HINGES

### Functions

Concealed hinges, designed for traditional profiles, with sash weight up to 130 kg.

Online data sheet



### Technical Features

This hinge is designed to be combined with reduced hardware dimensions in view, such as SUPRA 7.

### Materials

Corner support made of zamak  
 Connecting brackets and hinge plates made of zinc plated steel  
 Pins made of 304 grade stainless steel and aluminium bronze  
 Cams made of zinc plated steel


Table of maximum glass thickness [mm]

|      |     |     |     |     |     |     |      |      |      |      |      |      |      |
|------|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|
| 2800 | 35  | 29  | 25  | 22  | 19  | 17  | 16   | 14   | 13   | 12   | 12   |      |      |
| 2700 | 37  | 31  | 26  | 23  | 20  | 18  | 17   | 15   | 14   | 13   | 12   |      |      |
| 2600 | 39  | 32  | 28  | 24  | 21  | 19  | 18   | 16   | 15   | 14   | 13   | 12   |      |
| 2500 | 43  | 35  | 30  | 27  | 24  | 21  | 19   | 18   | 16   | 15   | 14   | 13   |      |
| 2400 | 43  | 35  | 30  | 27  | 24  | 21  | 19   | 18   | 16   | 15   | 14   | 13   |      |
| 2300 | 44  | 37  | 32  | 28  | 25  | 22  | 20   | 18   | 17   | 16   | 15   | 14   |      |
| 2200 | 46  | 39  | 33  | 29  | 26  | 23  | 21   | 19   | 18   | 17   | 15   | 14   |      |
| 2100 | 49  | 40  | 35  | 30  | 27  | 24  | 22   | 20   | 19   | 17   | 16   | 15   |      |
| 2000 | 51  | 43  | 36  | 32  | 28  | 26  | 23   | 21   | 20   | 18   | 17   | 16   |      |
| 1900 | 54  | 45  | 38  | 34  | 30  | 27  | 24   | 22   | 21   | 19   | 18   | 17   |      |
| 1800 | 57  | 47  | 40  | 35  | 31  | 28  | 26   | 24   | 22   | 20   | 19   | 18   |      |
| 1700 | 60  | 50  | 43  | 38  | 33  | 30  | 27   | 25   | 23   | 21   | 20   | 18   |      |
| 1600 | 60  | 53  | 46  | 40  | 35  | 32  | 29   | 27   | 25   | 23   | 21   | 18   |      |
| 1500 | 60  | 57  | 49  | 43  | 38  | 34  | 31   | 28   | 26   | 24   | 21   | 18   |      |
| 1400 | 60  | 60  | 52  | 46  | 40  | 36  | 33   | 30   | 28   | 24   | 21   | 18   |      |
| 1300 | 60  | 60  | 56  | 49  | 44  | 39  | 36   | 33   | 28   | 24   | 21   | 18   |      |
| 1200 | 60  | 60  | 60  | 53  | 47  | 43  | 39   | 33   | 28   | 24   | 21   |      |      |
| 1100 | 60  | 60  | 60  | 58  | 52  | 46  | 39   | 33   | 28   | 24   |      |      |      |
| 1000 | 60  | 60  | 60  | 60  | 57  | 47  | 39   | 33   | 28   |      |      |      |      |
| 900  | 60  | 60  | 60  | 60  | 58  | 47  | 39   | 33   |      |      |      |      |      |
| 800  | 60  | 60  | 60  | 60  | 58  | 47  | 39   |      |      |      |      |      |      |
| 700  | 60  | 60  | 60  | 60  | 58  | 47  |      |      |      |      |      |      |      |
| 600  | 200 | 500 | 600 | 700 | 800 | 900 | 1000 | 1100 | 1200 | 1300 | 1400 | 1500 | 1600 |


Table of maximum load capacity [kg]

|      |     |     |     |     |     |     |      |      |      |      |      |      |      |
|------|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|
| 2800 | 124 | 124 | 124 | 124 | 124 | 124 | 124  | 124  | 124  | 124  | 124  | 124  |      |
| 2700 | 126 | 126 | 126 | 126 | 126 | 126 | 126  | 126  | 126  | 126  | 126  | 126  |      |
| 2600 | 128 | 128 | 128 | 128 | 128 | 128 | 128  | 128  | 128  | 128  | 128  | 128  | 128  |
| 2500 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 130  | 130  | 130  |
| 2400 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 130  | 130  | 130  |
| 2300 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 130  | 130  | 130  |
| 2200 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 130  | 130  | 130  |
| 2100 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 130  | 130  | 130  |
| 2000 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 130  | 130  | 130  |
| 1900 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 130  | 130  | 130  |
| 1800 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 130  | 130  | 130  |
| 1700 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 130  | 130  | 127  |
| 1600 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 130  | 127  | 119  |
| 1500 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 130  | 128  | 119  | 112  |
| 1400 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 130  | 129  | 119  | 111  | 104  |
| 1300 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 129  | 119  | 111  | 103  | 97   |
| 1200 | 130 | 130 | 130 | 130 | 130 | 130 | 130  | 130  | 119  | 110  | 102  | 95   |      |
| 1100 | 130 | 130 | 130 | 130 | 130 | 130 | 119  | 109  | 101  | 94   |      |      |      |
| 1000 | 130 | 130 | 130 | 130 | 130 | 119 | 108  | 99   | 92   |      |      |      |      |
| 900  | 130 | 130 | 130 | 130 | 119 | 107 | 98   | 90   |      |      |      |      |      |
| 800  | 130 | 130 | 130 | 119 | 106 | 95  | 87   |      |      |      |      |      |      |
| 700  | 130 | 130 | 119 | 104 | 93  | 84  |      |      |      |      |      |      |      |
| 600  | 200 | 500 | 600 | 700 | 800 | 900 | 1000 | 1100 | 1200 | 1300 | 1400 | 1500 | 1600 |


### ADJUSTMENTS [mm]



Height:  
+2.5 / -1



Side:  
+1.5 / -1.5



Hinge compression:  
+1.4 / -0.6

| Item code | Description                    | PROFILE CROSS - SECTION | Hand | Base Raw | Anodised Elox | Painted | Trend/Gold Brass | Pieces per pack |
|-----------|--------------------------------|-------------------------|------|----------|---------------|---------|------------------|-----------------|
| 052831    | CHIC 130 ERRE - SASH HINGE SET | C007                    | RX   | X        |               |         |                  | 10              |
| 052832    | CHIC 130 ERRE - SASH HINGE SET | C007                    | LX   | X        |               |         |                  | 10              |