



GHIBO ONE-WAY M180 OUTWARD OPENING MECHANISMS

Functions

The one-way Ghibo out internal mechanism is housed in the hollow section of the profile and, via a window handle, moves the rods and locking points of outward-opening side-hung windows. It is equipped with an incorrect movement safety device.

Online data sheet



Technical Features

Ideal for outward-opening side-hung windows (Side Hung, doorways, etc.). This device is reversible and is ready to be fitted on either right or left sashes. The mechanism is equipped with an incorrect movement safety device and has a stroke of 36 mm (18 + 18). It is designed to accommodate a 7 mm square spindle and to be combined with all the window handles made by GIESSE, both of aluminium and brass, with a 43 mm fixing C/C distance. The product is secured to the sash profile with the screws supplied.

Materials

Case and connection devices to transmit motion and rotor made of zamak
Incorrect movement safety device made of stainless steel
Tubes and bushings of black polyamide
Stainless steel fixing screws

Overall dimensions

Example of application

Item code	Description	Opening	Technical notes	Backset	Base Raw	Anodised Elox	Painted	Trend/Gold Brass	Pieces per pack
04089	ONE-WAY MECHANISM M180 BS 30	Outward-opening side- hung window	stroke 36 mm	E= mm 30	X				5